

ULTRA LOW-LIGHT MARINE CAMERA

MODEL CRV-500C SKU C012800 UPC-A 811251020149

Nightwave is an ultra low-light camera system built around SIONYX's patented Black Silicon CMOS sensor. It allows all levels of mariners to easily spot obstacles and debris in moonless starlight without white light or expensive thermal cameras — navigating safely, avoiding collisions, and maximizing time on the water. With easy mounting and setup, Nightwave can stream video to a mobile device via WiFi or directly connect to other hardware via analog output, displaying clear color digital night vision.

CONNECTED	Seamless integration with major brand MFDs via the analog video output. Convenient installation flexibility with built in WiFi video streaming and communication.
RUGGED	IP67 rated, submersible to 3 ft for 30 minutes. You can safely use Nightwave in inclement weather conditions.
CAPABLE	<1 MLX MOONLESS STARLIGHT sensitivity allows you to see well beyond human eyesight & pick up a man-sized object at 150 meters.
AWARE	40° field of view increases situational awareness to spot unexpected obstacles, debris, markers, vessels, and more

CAMERA

SENSOR TYPE	CMOS
RESOLUTION	1920 X 1080
FRAME RATE	60 HZ
HORIZONTAL FOV	720P .MOV VIDEO
VISIBLE SPECTRUM	400-1100NM
FOCUS RANGE	10M TO INFINITY
LENS	16MM F/1.4

SYSTEM

DIGITAL MAGNIFICATION	1X - 3X
VIDEO OUT	NTSC/PAL
WIRELESS COMMUNICATIONS	WIFI + BLUETOOTH
POWER IN	12V DC

ENVIRONMENTAL

IP67 WATER/DUST RESISTANT
IEC61945 [V:15G H:9G]
-20°C TO +50°C
-20°C TO +80°C

RANGE PERFORMANCE	CLEAR WEATHER AT 1/4 MOON
DETECT MAN-SIZED TARGET	150 M

PHYSICAL

WEIGHT	870 G [1.9 LBS]
DIMENSIONS	127 x 127 x 152 MM [5 x 5 x 6 IN]
MOUNTING OPTIONS	TRIPOD OR RAMMOUNT:
	SINGLE 1/4" 20 CENTER MOUNT
	BULKHEAD MOUNT: 4 x 1/4" 20
	TOP-DOWN MOUNTING HOLES
MATERIAL	UV RESISTANT POLYCARBONATE

INCLUDED

CAMERA	INSTALL TEMPLATE
CABLE [5M]	USER MANUAL
MOUNTING HARDWARE	

EYESIGHT VS NIGHTWAVE





DEPTH: 127 MM | 5 IN



